








PITCH 1.0mm FPC CONNECTOR SMT TYPE

性能:

额定电流: 0.4A
额定电压: 50V
耐电压: 200V
接触电阻: $\leq 20m\Omega$
绝缘电阻: 500M Ω
工作温度: -20℃~+85℃

塑件 (材质): LCP, U194V-0
锁扣 (材质): LCP, U194V-0
插簧 (材质): 磷青铜, 镀锡/镀金
焊片 (材质): 磷青铜, 镀锡/镀金



适用电缆

孔位	A	B	C	D
2	1.00	3.10	6.85	8.15
3	2.00	4.10	7.85	9.15
4	3.00	5.10	8.85	10.15
5	4.00	6.10	9.85	11.15
6	5.00	7.10	10.85	12.15
7	6.00	8.10	11.85	13.15
8	7.00	9.10	12.85	14.15
9	8.00	10.10	13.85	15.15
10	9.00	11.10	14.85	16.15
11	10.00	12.10	15.85	17.15
12	11.00	13.10	16.85	18.15
13	12.00	14.10	17.85	19.15
14	13.00	15.10	18.85	20.15
15	14.00	16.10	19.85	21.15
16	15.00	17.10	20.85	22.15
17	16.00	18.10	21.85	23.15
18	17.00	19.10	22.85	24.15
19	18.00	20.10	23.85	25.15
20	19.00	21.10	24.85	26.15
21	20.00	22.10	25.85	27.15
22	21.00	23.10	26.85	28.15
23	22.00	24.10	27.85	29.15
24	23.00	25.10	28.85	30.15
25	24.00	26.10	29.85	31.15
26	25.00	27.10	30.85	32.15
27	26.00	28.10	31.85	33.15
28	27.00	29.10	32.85	34.15
29	28.00	30.10	33.85	35.15
30	29.00	31.10	34.85	36.15

X. ± 0.3	X° ± 5°	UNITS	mm	NAME (INTENDED USE) 1.0mm FPC (A型) 立贴正脚 (H±2.0)				深圳市鸿锐盛电子有限公司			
.X ± 0.25	.X° ± 2°	MAT'L									
.XX ± 0.20	.XX° ± 1°	FINISH		PART NO. (INTENDED USE) 1.0K-N-nPB				TITLE: 1.0mm FPC (A型) 立贴正脚 (H±2.0)			
.XXX ± 0.10	.XXX° ± 0.5°										
APDR:				DWG NO.:							
CHKD:				Q'TY							
DR:											
				SCALE				SHEET			
				1/1				1/1			
								REV.			
								A			